



UNITED STATES PATENT AND TRADEMARK OFFICE

cen
UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/776,163	02/12/2004	Ofer Ben-Zur	29066	3782

7590
Martin Moynihan
PRTSI, Inc.
P.O. Box 16446
Arlington, VA 22215

EXAMINER

NGUYEN, LAM S

ART UNIT	PAPER NUMBER
2853	

MAIL DATE	DELIVERY MODE
05/11/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary	Application No. 10/776,163	Applicant(s) BEN-ZUR, OFER	
	Examiner LAM S. NGUYEN	Art Unit 2853	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 25 April 2007.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-32 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-32 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 29 November 2006 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413) |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____ |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Continued Examination Under 37 CFR 1.114

A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 04/25/2007 has been entered.

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

1. Claims 13-19, 20-21 are rejected under 35 U.S.C. 103(a) as being unpatentable over Iwatsuki et al. (US 2003/0197772 A1) in view of Codos (US 6755518), Rasmussen et al. (US 6536894), and Rezanka (US 5757407).

Regarding to claim 13:

Iwatsuki et al. discloses a printing machine comprising:

a rigid frame (*FIG. 1, element 1*);

a linear motion X axis stage (*FIG. 1, elements 11, 11a-b*) mounted on said frame;

a printing table assembly (*FIG. 1, elements 12, 13, 15*) configured to move back

and forth on said linear X axis stage (*FIG. 1: The stage 11 linearly moves from FRONT SIDE to REAR SIDE and versa*);

Art Unit: 2853

a linear motion Y axis stage (*FIG. 1, elements 2-4*) mounted on said frame perpendicular to said linear X axis stage, above said printing table assembly (*FIG. 1: The carriage 4 moves along a direction perpendicular to the moving direction of printing table assembly 11*);

an array of inkjet nozzles for applying ink on a media loaded on said printing table assembly, said array of inkjet nozzles (*FIG. 1, element 5 and paragraph [0066]: The printing head 5 has a plurality of nozzles*) being mounted on said linear Y axis stage for linear motion perpendicular to said X axis stage (*FIG. 1: The carriage 4 moves the printhead 4 across the printing table assembly*).

- Iwatsuki et al., however, does not teach a curing unit located above said printing table assembly and arranged to cure ink on media on said printing assembly, wherein said curing unit is an infrared system or a hot air blowing unit (**Regarding to claims 14-15**), and wherein at least part of said printing table assembly is a vacuum table (**Regarding to claim 18**).

Codos discloses an ink jet printing apparatus mounted on a rigid frame (*FIG. 1, element 111*) and including an ink jet printhead assembly (*FIG. 1, element 125*) for forming images on a printing medium (*FIG. 1, element 15*) conveyed by a vacuum conveyor (*FIG. 1, element 105, 121*) and a curing unit located above the printing medium to cure ink deposited on the printing medium, wherein said curing unit is an infrared system or a hot air blowing unit (*FIG. 1, elements 124, 126; column 8, lines 62-64: Heating by forced hot air is preferred, although other heat sources, such as infrared heaters can be used*).

Therefore, it would have been obvious for one having ordinary skill in the art at the time

Art Unit: 2853

invention was made to modify Iwatsuki et al.'s printing apparatus to include a curing unit to cure ink deposited on the printing medium as disclosed by Codos. The motivation for doing so would have been to cure the ink upon its contacting the substrate (printing medium) to prevent ink spreading and wicking that affect printing quality as taught by Codos (*column 2, lines 65-67*).

- In addition, Iwatsuki et al. does not teach an ironing unit located above said printing table assembly and arranged to iron media on said printing assembly before printing thereon.

Rasmussen et al. discloses an ink jet printing apparatus including an ink jet printhead (*FIG. 2B, element 14*) for forming images on a printing medium conveyed by a conveyor (32) and an ironing unit located above said printing medium and arranged to iron said printing media before printing thereon (*FIG. 2B, elements 201', 202; column 3, lines 32-38: Heating and pressing the print media upstream of printing to flatten print media prior to ink jet printing thereon*).

Therefore, it would have been obvious for one having ordinary skill in the art at the time invention was made to modify Iwatsuki et al.'s printing apparatus to include an ironing unit located above the printing medium to iron the printing media before printing as disclosed by Rasmussen et al. The motivation for doing so would have been to provide a flat and stable media for printing in order to improve image quality as taught by Rasmussen et al. (*column 4, lines 19-24*).

- Iwatsuki et al., in addition, is silent wherein said inkjet nozzles include drop-on-demand piezoelectric inkjet nozzles or continuous piezoelectric inkjet nozzles and does not teach wherein during said applying said printing table assembly passes by said array of inkjet nozzles in said

Art Unit: 2853

back and forth movements said array of inkjet nozzles is substantially static on said linear Y axis.

Rezanka discloses an ink jet printing apparatus comprising an array of ink jet nozzles including either drop-on-demand piezoelectric inkjet nozzles or continuous piezoelectric inkjet nozzles (*column 12, lines 10-13*) for ejecting ink droplets to form images on a printing medium conveyed on a printing table assembly, wherein during applying ink drops from the nozzle array to the printing table assembly passing by said nozzle array in back and forth movements, the nozzle array is substantially static (*column 1, lines 47-53*).

Therefore, it would have been obvious for one having ordinary skill in the art at the time invention was made to structure the inkjet printhead in Iwatsuki et al.'s printing apparatus to be stationary during the printing operation as disclosed by Rezanka. The motivation for doing so would have been to increase printing speeds as taught by Rezanka (*column 4, lines 52-55*).

- **Iwatsuki et al. also teaches the following claimed invention:**

Regarding to claim 16: wherein said printing table assembly comprises a media-holding plate (*FIG. 5A-D, element 15*) and an openable cover (*FIG. 1, element 14*) pivotally coupled to said media-holding plate for holding said media firmly against said plate (*FIG. 5A-D*).

Regarding to claim 17: wherein said media-holding plate (*FIG. 5A-D, element 15*) includes a raised portion (*FIG. 5A-D, element 12*), and said cover includes a window (*FIG. 5A-D: The window is defined by the inner frame 19 of the frame structure (cover) 14*) of the same shape and slightly larger than said raised portion (*FIG. 5A-D, elements 12 and 19: The width of the inner frame (window) 19 is slightly wider than that of the raise portion 12*).

Regarding to claim 19: wherein said printing table assembly is a flattened plate (*FIGs.*

Art Unit: 2853

5A-D, elements 12-13 and 15).

2. Claims 1-3, 7-8, 22, 27-28, 30-31, and 32 are rejected under 35 U.S.C. 103(a) as being unpatentable over Iwatsuki et al. (US 2003/0197772 A1) in view of Morita et al. (US 6879378) and Rezanka (US 5757407).

Iwatsuki et al. discloses a printing machine comprising:

a rigid frame (*FIG. 1, element 1*);

a first linear motion X axis stage (*FIG. 1, elements 11, 11a-b*) mounted on said frame;

a first printing table assembly (*FIG. 1, elements 12, 13, 15*) configured for moving back and forth on said linear X axis stage (*FIG. 1: The stage 11 linearly moves from FRONT SIDE to REAR SIDE and versa*);

a linear motion Y axis stage (*FIG. 1, elements 2-4*) mounted on said frame perpendicular to said linear X axis stage, above said printing table assembly (*FIG. 1: The carriage 4 moves along a direction perpendicular to the moving direction of printing table assembly 11*);

an array of inkjet nozzles for applying ink on a media loaded on said printing table assembly, said array of inkjet nozzles (*FIG. 1, element 5 and paragraph [0066]: The printing head 5 has a plurality of nozzles*) being mounted on said linear Y axis stage for linear motion perpendicular to said X axis stage (*FIG. 1: The carriage 4 moves the printhead 4 across the printing table assembly*).

- Iwatsuki et al., however, does not teach a second linear motion X axis stage mounted on

said frame parallel to said first axis stage, and arranged for operation independently of said first axis stage or a second printing table assembly movable on said linear X axis stage base independently of said first printing table assembly.

Morita et al. discloses an image forming apparatus for forming a pattern on each of at least two workpieces positioned on associated linearly movable support tables/stages, wherein the linearly movable support tables/stages (*FIG. 6, elements 10, 20*) are mounted on the same frame (*FIG. 6, element 5*), being parallel, and arranged for independently operation (*FIG. 6: The two tables 10, 20 move along the parallel directions L1 and L2 and each having independent function at a time*).

Therefore, it would have been obvious for one having ordinary skill in the art at the time invention was made to modify Iwatsuki et al.'s printing apparatus to include a second table/stage that is parallel and independently operates from the first table/stage as disclosed by Morita et al. The motivation for doing so would have been to be able to alternatively transfer the tables between a load/unload position and an image/pattern forming position and alternatively form images/patterns on the tables so at least two workpieces can be processed simultaneously in order to increase the throughput of the apparatus as taught by Morita et al. (*column 3, lines 45-59*).

- Iwatsuki et al., in addition, is silent wherein said inkjet nozzles include drop-on-demand piezoelectric inkjet nozzles or continuous piezoelectric inkjet nozzles and does not teach wherein during said applying said printing table assembly passes by said array of inkjet nozzles in said back and forth movements said array of inkjet nozzles is substantially static on said linear Y axis.

Rezanka discloses an ink jet printing apparatus comprising an array of ink jet nozzles including either drop-on-demand piezoelectric inkjet nozzles or continuous piezoelectric inkjet nozzles (*column 12, lines 10-13*) for ejecting ink droplets to form images on a printing medium conveyed on a printing table, wherein during applying ink drops from the nozzle array on a printing table assembly passing by said nozzle array in back and forth movements, the nozzle array is substantially static (*column 1, lines 47-53*).

Therefore, it would have been obvious for one having ordinary skill in the art at the time invention was made to structure the inkjet printhead in Iwatsuki et al.'s printing apparatus to be stationary during the printing operation as disclosed by Rezanka. The motivation for doing so would have been to increase printing speeds as taught by Rezanka (*column 4, lines 52-55*).

- **Iwatsuki et al. also teaches the following claimed invention:**

Regarding to claims 2, 27: wherein said printing table assembly comprises a media-holding plate (*FIG. 5A-D, element 15*) and an openable cover (*FIG. 1, element 14*) pivotally coupled to said media-holding plate for holding said media firmly against said plate (*FIG. 5A-D*).

Regarding to claims 3, 28: wherein said media-holding plate (*FIG. 5A-D, element 15*) includes a raised portion (*FIG. 5A-D, element 12*), and said cover includes a window (*FIG. 5A-D: The window is defined by the inner frame 19 of the frame structure (cover) 14*) of the same shape and slightly larger than said raised portion (*FIG. 5A-D, elements 12 and 19: The width of the inner frame (window) 19 is slightly wider than that of the raise portion 12*).

Regarding to claim 32: wherein said back and forth movement comprises a circular movement (*paragraph [0008]: The movement of a garment/fabric can be conveyed by belts that are moved circularly*).

3. Claims 6, 9-11, 24-26, and 29 are rejected under 35 U.S.C. 103(a) as being unpatentable over Iwatsuki et al. (US 2003/0197772 A1) in view of Morita et al. (US 6879378) and Rezanka (US 5757407), as applied to claims 1 and 22, and further in view of Codos (US 6755518).

Iwatsuki et al., as modified, discloses the claimed invention as discussed above except a curing unit located above each said printing table assembly and arranged to cure ink on media on said printing assembly (**Regarding to claims 9, 24**), wherein said curing unit is an infrared system or a hot air blowing unit (**Regarding to claims 10-11, 25-26**), and wherein at least part of said printing table assembly is a vacuum table (**Regarding to claims 6, 29**).

Codos discloses an ink jet printing apparatus including an ink jet printhead (*FIG. 1, element 125*) for forming images on a printing medium (*FIG. 1, elements 15*) conveyed by a vacuum conveyor (*FIG. 1, element 105, 121*) and a curing unit located above the printing medium to cure ink deposited on the printing medium, wherein said curing unit is an infrared system or a hot air blowing unit (*FIG. 1, elements 124, 126; column 8, lines 62-64: Heating by forced hot air is preferred, although other heat sources, such as infrared heaters can be used*).

Therefore, it would have been obvious for one having ordinary skill in the art at the time invention was made to modify Iwatsuki et al.'s printing apparatus (as modified) to include a curing unit to cure ink deposited on the printing medium as disclosed by Codos. The motivation for doing so would have been to cure the ink upon its contacting the substrate (printing medium) to prevent ink spreading and wicking that affect printing quality as taught by Codos (*column 2, lines 65-67*).

Art Unit: 2853

4. Claims 12 and 23 are rejected under 35 U.S.C. 103(a) as being unpatentable over Iwatsuki et al. (US 2003/0197772 A1) in view of Morita et al. (US 6879378) and Rezanka (US 5757407), as applied to claims 1 and 22, and further in view of Rasmussen et al. (US 6536894).

Iwatsuki et al., as modified, discloses the claimed invention as discussed above except an ironing unit located above each said printing table assembly and arranged to iron media on said printing table assemblies.

Rasmussen et al. discloses an ink jet printing apparatus including an ink jet printhead (*FIG. 2B, element 14*) for forming images on a printing medium conveyed by a conveyor (32) and an ironing unit located above said printing medium and arranged to iron said printing media before printing thereon (*FIG. 2B, elements 201', 202; column 3, lines 32-38: Heating and pressing the print media upstream of printing to flatten print media prior to ink jet printing thereon*).

Therefore, it would have been obvious for one having ordinary skill in the art at the time invention was made to modify Iwatsuki et al.'s printing apparatus (as modified) to include an ironing unit located above the printing medium to iron the printing media before printing as disclosed by Rasmussen et al. The motivation for doing so would have been to provide a flat and stable media for printing in order to improve image quality as taught by Rasmussen et al. (*column 4, lines 19-24*).

5. Claims 4-5 are rejected under 35 U.S.C. 103(a) as being unpatentable over Iwatsuki et al. (US 2003/0197772 A1) in view of Morita et al. (US 6879378) and Rezanka (US 5757407), as applied to claim 1, and further in view of Nakamura et al. (US 2003/0142167 A1).

Iwatsuki et al., as modified, discloses the claimed invention as discussed above except

wherein said linear motion X axis stage is a linear motor driven stage and said linear motion Y axis stage is a linear motor driven stage.

Nakamura et al. discloses an ink jet printing apparatus comprising a linear motion X axis stage (*FIG. 9, elements 19, 52-53*) to convey an ink jet printhead (*FIG. 9, element 22*) to form images on a printing medium (*FIG. 9, element 12*) positioned on a printing table (*FIG. 9, element 49*) conveyed by a linear motion Y axis stage (*FIG. 9, elements 21, 54, 56*), wherein both X and Y linear motion stages are linear motor driven stages (*paragraphs [0103]-[0104]: An X slider/stage 53 contains a linear motor. A Y slider/stage 56 contains a linear motor. The X and Y sliders move when the associated built-in linear motor is operated*).

Therefore, it would have been obvious for one having ordinary skill in the art at the time invention was made to modify Iwatsuki et al.'s printing apparatus (as modified) to move/drive the stages by linear motors as disclosed by Nakamura et al. The motivation for doing so would have been because it is possible to control a position of the ink jet head supported by the X stage and a position of the printing table supported by the Y stage very precisely as taught by Nakamura (*paragraph [0105]*).

Response to Arguments

Applicant's arguments with respect to claims 1, 13, and 22 have been considered but are moot in view of the new ground(s) of rejection.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to LAM S. NGUYEN whose telephone number is (571)272-2151. The examiner can normally be reached on 7:00AM - 3:30PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, STEPHEN D. MEIER can be reached on (571)272-2149. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

A handwritten signature in black ink, appearing to read 'Lam Son Nguyen', with a stylized, cursive script.

LAM SON NGUYEN